

BLS 2600 ne»xt

ELECTRIC RESPIRATOR WITH DUST FILTER

BLS 2600 ne»xt electric respirator is an assisted ventilation system to be used with a full face mask and dust filter.

It supplies the user with filtered ambient air and thanks to the constant air flow and the absence of respiratory effort it is the ideal solution for heavy use.

BLS 2600 ne»xt guarantees excellent usability, it is impact resistant and comes with a full range of accessories and spare parts.



FILTER

The TMP3 filter provides high filtration for long periods. It is protected by an easily removable ring nut. A practical anti-water cap protects the filter during the decontamination shower phase.



AUTOMATIC FLOW ADJUSTMENT

Thanks to the automatic flow adjustment, BLS 2600 ne»xt guarantees a flow of 160 l/min even when the filter is clogged when not in use.

BATTERY

The performing and light battery guarantees a duration of more than 10h in maximum comfort. For the charging phase, BLS 2600 ne»xt is equipped with a sturdy and ergonomic connector, while the status of charge is returned both by the LEDs on the motor unit and on the battery charger.

COMPATIBLE DEVICES

Optionally, the BLS 5150 and BLS 5400 full face masks can be combined with the electric respirator. All mask models are equipped with a universal fitting EN 148-1 on which the corresponding fitting of the corrugated hose is inserted. The masks are PPE certified according to the EN 136:1998 standard.

COMFORT

The PVC belt with adjustment buckles guarantees an optimal hold around the waist, while the padded support provides maximum comfort and perfect decontamination thanks to the quick release system.



STORAGE KIT

Possibility of storage in maximum safety thanks to the DIN cap for the motor unit, the filter cap, the hose that can be closed on itself and the practical and sturdy container box, equipped with four handles, gasket and arrangement for the padlock.



SOUND/VISUAL/VIBRANT FEEDBACK

The innovative management system provides the operator with the following feedbacks via the 3 coloured LEDs: battery charge status, low battery alarm, flow block alarm, filter clogging alarm, recharging status. All alarms are also signalled by a sound and a vibration.

BLS 2600 ne»xt

ELECTRIC RESPIRATOR WITH DUST FILTER

COMPONENTS

The BLS 2600 ne»xt electric respirator consists of:

- Motorised filtering unit, powered by NiMh rechargeable battery (7.2 V 9 Ah)
- Corrugated rubber hose connecting the electric respirator mask
- Full face mask to choose between models 5150 and 5400*
- TMP3 high efficiency dust filter, replaceable*
- Water cap and storage cap
- Battery charger

* Sold separately

TECHNICAL DATA


MINIMUM FLOW*	160 l/min
WEIGHT (excluding corrugated tube and mask)	1250 g
CHARGING TIME	6 hours

* Declared by the manufacturer

LIGHT/SOUND INDICATORS

Indicators: light signal (green, yellow, red, blue) for battery charge level, acoustic alarm for low battery.

Filter clogging monitoring with acoustic alarm.



BLS 2600 ne»xt

CODE	DESCRIPTION	WEIGHT (Kg)	BOX WEIGHT (Kg)
8103001	Electric respirator	4,40	5,12

FILTERS

CODE	ITEM	DESCRIPTION	WEIGHT (g)	QTY/PACK	PACK WEIGHT (g)
8117003	TMP3	Dust filter	165	6	1095
8011001	Prefilter	Prefilter for TMP3	3	50	150

FULL FACE MASKS

CODE	ITEM	SIZE	DESCRIPTION	WEIGHT (g)	QTY/PACK	QTY/BOX	BOX WEIGHT (Kg)
8001035	BLS 5150	U	Full face mask	530	1	4	3,42
8001039	BLS 5400	U	Full face mask	540	1	4	3,46

ACCESSORIES/SPARE PARTS

CODE	DESCRIPTION	WEIGHT	SALE QTY
8118003	SK-89 Container box	1,56 kg	1
8118002	SK-88 Kit corrugated hose	500 g	1
8118004	SK-90 Padded waistband	125 g	1
8118005	SK-91 PVC belt	239 g	1
8118006	SK-92 Flow meter	29 g	1
8118007	SK-93 Battery charger	265 g	1
8118008	SK-94 Anti-contamination kit:		
	n°1 DIN cap**		
	n°1 Water lid**	55 g	1
	n°1 Storage lid**		
8118009	SK-95 Filter ring	97 g	1
8118010	SK-96 Battery*	404 g	1
8118011	SK-97 Motor*	90 g	1

* Authorized distributor

** Anti-contamination kit sold complete with DIN cap, water lid and storage lid

BLS 2600 ne»xt

ELECTRIC RESPIRATOR WITH DUST FILTER

COMPATIBLE DEVICES



Full face masks BLS 5400 - BLS 5150

CERTIFICATIONS

- EN 12942:2009 TM3P R SL
- Regulation UE 425/2016
- European Directive EMC 2014/30/UE
- EN 12942:2009
- EN 61000-6-2:2019
- EN 61000-6-3:2007/A1:2011/AC:2012-08
- Dust and water protection degree IP66 according to EN60529

STORAGE

DURATION	5 years
TEMPERATURE	-10°C/+50°C
RELATIVE HUMIDITY	75%

IMPORTANT

BLS shall assume no liability whatsoever, direct or indirect, deriving from incorrect or improper use of the devices and failure to comply with the instructions. The user is responsible for determining the suitability of the products for the intended use.